



MADE IN USA

LUBRIKON®
QUALITY OILS

2 - CYCLE

AIR COOLED

LUBRIKON 2T

LUBRIKON 2T is an oil, design to fulfill the highest standard of oil behavior on air-cooled two-stroke engines, protects the motor ring to avoid getting stuck together and damage on piston deposits. It must not be used were TC-W3 oils are required.

Recommended in small 2-stroke engines where SAE 30 lubricants should be used, such as motorcycle engines, small outboard motors, scooters, lawnmowers, and chainsaws, among others.

BENEFITS TO THE COSTUMER

- Provides a quick start
- Protects against rust and corrosion.
- Minimizes the formation of deposits / sludge in the combustion chamber, spark plugs and exhaust system.
- Prevents rust formation and minimizes wear on engine parts.

APPLICATIONS

- Air-cooled 2-cycle engines.
- Engines that require API TC performance level oil.
- Suitable for the following 2-stroke engines:
 - Homelite
 - Husqvarna
 - Poulan
 - Pioneer
 - Stihl
 - McCulloch

Features	ASTM Method	LUBRIKON 2T
SAE grade		30
Flash point, COC, °C (°F)	ASTM D92	207 / 405
Pour point, °C (°F)	ASTM D97	-18/0
Color	ASTM D-1500	3,5
Gravity API, 60°F		23,0
Viscosity cSt @ 40°C	ASTM D445	52,8
SUS @ 100°C	ASTM D445	9,3

*The values shown in the table of typical characteristics are approximate or referential, as an indication and do not constitute a guarantee. These values can be modified without prior notice. The results of the production lots may differ slightly. This does not affect the performance of the product.

Presentations



Storage

The store should not exceed 140 °F temperature, the products should not be exposed to the direct incidence of the sun or places of low temperatures.



Scan QR for Contact